

ChargePoint 6000 Series

High-output, reliable AC charging for any EV today and tomorrow



Charge any EV, including Tesla

Simplify site planning and save money with NACS (Tesla) and J1772 connectors in each port. Allow drivers to use any station regardless of their connector type with ChargePoint® Omni Port.

Reduce charging times and stay in control

Charge faster and prepare your site for tomorrow's vehicles with up to 19.2kW (80A) per port. Avoid electrical upgrades and control costs with advanced energy management features.

Reduce repair and service costs

Diagnose faults remotely and save money on parts and labor with individually serviceable components that can be swapped on-site. Cut-resistant cable options prevent theft, while ChargePoint® Protect detects cable cutting in real time and triggers audible and visual alarms across nearby stations.



ChargePoint® CP6000 paired with the ChargePoint Platform enables complete driver and charger management and rich insights across all stations and sites. Configure stations to fit your needs, manage the driver experience, access actionable reporting, and much more.

Specifications

| Feature | Description |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Connectivity | 4G LTE with GSM as backup, Wi-Fi LAN |
| Interface | 8" (inch) interactive display with full color, UV protection, gesture touch controls and multi- language support |
| Authentication | RFID, tap to charge (NFC), remote via mobile app or in vehicle |
| Payment | EMV contactless credit/debit reader -CHIP models also have an EMV chip reader |
| Connector | J1772, optional with Omni Port (J1772 and NACS) |
| ISO 15118 standard | Supported |
| Network communication protocol | OCPP 2.0.1 |
| Certifications | CTEP/NTEP, UL Listed |
| Status indicators | Multi-color status LED |

Configuration options

| Feature | Description |
|------------------|------------------------------------------|
| Power | 50A (up to 12kW), 80A (up to 19.2kW) |
| Number of ports | Single, dual |
| Mounting options | Pedestal, wall |
| Cable length | 18', 23' |
| FHWA | Buy American compliant options available |

Pedestal mount



CP6611B-50A-L5.5 CP6611B-80A-L5.5 CP6011B-80A-L5.5 Single port, 18' cable



CP6621B-50A-L5.5 CP6621B-80A-L5.5 CP6021B-80A-L5.5 Dual port, 18' cable



CP6613B-50A-L5.5 CP6613B-80A-L5.5 CP6013B-80A-L5.5 Single port, 18' cable

Wall mount



CP6623B-50A-L5.5 CP6623B-80A-L5.5 CP6023B-80A-L5.5 Dual port, 18' cable

Let's get started

We're always here to help you identify your charging goals, advise on the best approach and help evaluate your site.

Connect with an Expert











