

RFID CARD


NOTES & REQUIREMENTS

- Minimum 1/8" margin for non-bleeding artwork
- Provide 1/4" bleed for artwork extending beyond card edge
- Any raster images must be embedded, CMYK, minimum 300dpi
- Convert all fonts to outlines
- Any spot colors will be converted to process; however, indicate Pantone color spec for reference.
- CMYK coverage should not exceed 220%


FRACTION	DECIMAL	METRIC
1-3/8"	1.375"	34.9 mm
2-3/8"	2.375"	60.3 mm

Enter artwork here
(use CUSTOMER ARTWORK layer)

Indicate any PMS colors




 Customizable

 Non-customizable
Reserved for ChargePoint content only, not editable

Trim

Bleed



PMS 158 Orange
PMS 5425 Gray

Fonts converted to outlines


TRIM

SAMPLE CUSTOMER ARTWORK



RFID MAILER


- Customizable
- Non-customizable
Reserved for ChargePoint content only, not editable




BACK PANEL
Use either space A or B, depending on whether kits will be distributed through the mail (space A) or in person (space B).




FRONT PANEL
This front panel is fully customizable.



GATE FOLD PANEL
(not visible until trifold is opened)
This panel is reserved for ChargePoint content and is not customizable.



INSIDE SPREAD
This panel is reserved for ChargePoint content and is not customizable.
Customized RFID card will go inside this spread. It will be positioned as shown.



NOTES & REQUIREMENTS

- Submit artwork in Illustrator EPS format
- Convert fonts to outlines
- Link any raster images (do not embed). Images must be minimum 300 dpi, CMYK color.
- Provide 1/8" bleed for any graphics that extend beyond trim.


Flat size: 8.26" x 13.125"

Final folded size: 6.25" x 4.375"

SAMPLE CUSTOMER ARTWORK

CUSTOMIZABLE AREAS


Highlighted in Yellow



BACK PANEL



FRONT PANEL



INSIDE SPREAD

